

**AMENDMENTS TO THE CLAIMS**

The following listing of claims will replace all prior versions and listings of claims in the application.

**LISTING OF CLAIMS**

1. (Currently Amended)      A protective device for a load branch circuit, comprising:  
  
    a first protective element within the protective device to provide motor-protection of a motor outside of the protective device and line protection; and  
  
    an integral second protective element within the protective device, the second protective element being connected in series with the first protective element and located on a line side of the first protective element, including a fuse, to provide short-circuit protection of the first protective element and the motor, wherein the second protective element is designed to provide overload protection for an electronic switching device between the protective device and the motor, the electronic switching device being in series with the first protective element, and wherein the first protective element includes an overload relay in series with the second protective element; and  
  
    a switch within the protective device for switching off the electronic switching device in the event of an overload, the switch being connected to the overload relay in parallel.
2. (Cancelled)
3. (Previously Presented)      The protective device as claimed in claim 1, wherein the fuse is transferrable from its operating position into a maintenance position.

4. (Previously Presented) The protective device as claimed in claim 3, further comprising:  
a locking mechanism to secure the maintenance position.

5. (Currently Amended) The protective device as claimed in claim 1, further comprising:  
an auxiliary switch within the protective device to signal the status of the fuse.

6. (Cancelled)

7. (Previously Presented) The protective device as claimed in claim 1, wherein a trip  
response of the first protective element is coordinated with the rating of a switching device.

8. (Previously Presented) An arrangement comprising:  
the protective device as claimed in claim 1; and  
the switching device, wherein the protective device and the switching device include  
widths of the same dimensions.

9. (Currently Amended) The protective device as claimed in ~~claim 1~~claim 8, wherein the  
fuse is transferable from its operating position into a maintenance position.

10. (Currently Amended) The protective device as claimed in ~~claim 1~~claim 8, further  
comprising:  
an auxiliary switch within the protective device to signal the status of the fuse.

11. (Currently Amended) A protective device for a load branch circuit, comprising:

first means for providing ~~motor~~ protection of a motor and line protection, the first means being located within the protective device; and

an integral second means located within the protective device and connected in series with the first protective means and located on a line side of the first protective means, including a fuse, for providing short-circuit protection of the first protective element and the motor, wherein the second means is designed to provide overload protection for an electronic switching device located between the protective device and the motor, the electronic switching device being in series with the first protective means, and wherein the first means includes an overload relay in series with the second protective means; and

a switch within the protective device for switching off the electronic switching device in the event of an overload, the switch being connected to the first means in parallel.

12. (Cancelled)

13. (Previously Presented) The protective device as claimed in claim 11, wherein the fuse is transferable from its operating position into a maintenance position.

14. (Previously Presented) The protective device as claimed in claim 13, further comprising:  
means for securing the maintenance position.

15. (Previously Presented) The protective device as claimed in claim 11, further comprising  
means for signaling the status of the fuse.

16. (Cancelled)

17. (Previously Presented) The protective device as claimed in claim 11, wherein a trip response of the first means is coordinated with the rating of a switching device.

18. (Previously Presented) An arrangement comprising:

the protective device as claimed in claim 11; and

the switching device, wherein the protective device and the switching device include widths of the same dimensions.

19. (Previously Presented) The protective device as claimed in claim 11, wherein the fuse is transferable from its operating position into a maintenance position.

20. (Previously Presented) The protective device as claimed in claim 11, further comprising:  
means for signaling the status of the fuse.

21. (Previously Presented) The protective device as claimed in claim 1, wherein the protective device is configured to be directly plugged onto the switching device.